



Technical parameters

ADD-ONS



Order Code:	iA-GRS4
Supported Media:	RS485
Power Consumption on Bus:	None
Isolation Type:	Board-to-board Galvanic Isolated
Dimensions:	35x30 mm



Order Code:	iA-ZGB
Supported Media:	Zigbee
Power Consumption on Bus:	None
Isolation Type:	None
Dimensions:	35x30 mm



Order Code:	iA-BUS
Supported Media:	iNELS BUS
Power Consumption on Bus:	None
Isolation Type:	None
Dimensions:	35x30 mm

Technical parameters

ADD-ONS



Supported Brand	Order Code	Terminal Name	Communication Line
Samsung	iA-VSM	F1-F2 / R1-R2	NASA
Daikin	iA-VDK	F1-F2	D3 Net
Hitachi	iA-VHT	1-2	TCC Link
LG	iA-VLG	A-B	Inter A-B
Mitsubishi Electric	iA-VME	M1-M2	M-Net TB3/7
Mitsubishi Heavy	iA-VMH	A-B	S Slink I/II
Midea/Chigo	iA-VMD	X-Y-E	X Y E
Panasonic/Sanyo	iA-VPA	U1-U2	S3 Net
Toshiba	iA-VTO	U1-U2	TCC Link

License

iL-P100:	100 BMS Points License
iL-P500:	500 BMS Points License
iL-P1000:	1000 BMS Points License
iL-VRF-U1:	1 Unit VRF License
iL-VRF-C1:	1 Channel - 64 Unit VRF License
iL-VRF-C2:	2 Channel - 128 Unit VRF License

